UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/087,779	03/05/2002	Thomas L. Johnson	1875.2050000	8819
26111 STERNE KES	7590 01/17/2007 SLER, GOLDSTEIN & FO	)X PLLC	EXAM	INER
1100 NEW YO	RK AVENUE, N.W.	ATELO	1875.2050000 8819  EXAMINER  SEFCHECK, GREGORY B	GREGORY B
WASHINGTO	N, DC 20005		ART UNIT	PAPER NUMBER
			2616	
SHORTENED STATUTOR	Y PERIOD OF RESPONSE	NOTIFICATION DATE	DELIVERY MODE	
3 MO	NTHS	01/17/2007	ELECTRONIC	

# Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Notice of this Office communication was sent electronically on the above-indicated "Notification Date" and has a shortened statutory period for reply of 3 MONTHS from 01/17/2007.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

fadkt@skgf.com

			51
	Application No.	Applicant(s)	•
	10/087,779	JOHNSON ET AL.	
Office Action Summary	Examiner	Art Unit	
	Gregory B. Sefcheck	2616	
The MAILING DATE of this communication appeariod for Reply	pears on the cover sheet wit	h the correspondence address	
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D  - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period  - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	OATE OF THIS COMMUNIC 136(a). In no event, however, may a re- will apply and will expire SIX (6) MON' e, cause the application to become AB.	CATION.  Sply be timely filed  ITHS from the mailing date of this communication  ANDONED (35 U.S.C. § 133).	
Status			
1) Responsive to communication(s) filed on 15 N	lovember 2006.		
2a) ☐ This action is <b>FINAL</b> . 2b) ☑ This	s action is non-final.		
3) Since this application is in condition for allowated closed in accordance with the practice under the condition of the			is
Disposition of Claims			
<ul> <li>4)  Claim(s) 1-39 is/are pending in the application 4a) Of the above claim(s) is/are withdra</li> <li>5)  Claim(s) is/are allowed.</li> <li>6)  Claim(s) 1-39 is/are rejected.</li> <li>7)  Claim(s) is/are objected to.</li> <li>8)  Claim(s) are subject to restriction and/or</li> </ul>	awn from consideration.		
Application Papers			
9) The specification is objected to by the Examine			
10) The drawing(s) filed on is/are: a) acc			
Applicant may not request that any objection to the			(d)
Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the E			(u).
Priority under 35 U.S.C. § 119			
<ul> <li>12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority document</li> <li>2. Certified copies of the priority document</li> <li>3. Copies of the certified copies of the priority application from the International Bureat</li> <li>* See the attached detailed Office action for a list</li> </ul>	nts have been received. Its have been received in A prity documents have been au (PCT Rule 17.2(a)).	pplication No received in this National Stage	
Attachment(s)  1)	4) ☐ Interview §	Summary (PTO-413)	
2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	Paper No(s	s)/Mail Date formal Patent Application	

Application/Control Number: 10/087,779 Page 2

Art Unit: 2616

#### **DETAILED ACTION**

 Applicant's Pre-Appeal Conference Request filed 11/15/2006 is acknowledged.

- In view of the required new rejections below, prosecution has been reopened.
- Claims 1-39 remain pending.

#### Claim Rejections - 35 USC § 101

1. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

- 2. Claims 1-26 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter.
  - Regarding Claims 1, 14, and 15,

The claimed invention is not directed to a practical application because claims 1, 14, and 15 do not require any physical transformation and the invention as claimed does not produce a useful, concrete, and tangible result.

The claims should be amended to include such practical application as is supported by the original disclosure, such as transmission of the packet after processing based upon the test results from the program modules.

## Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35
U.S.C. 102 that form the basis for the rejections under this section made in this
Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 4. Claims 1, 4, 5, 10-15, 18-19, 24-27 are rejected under 35 U.S.C. 102(e) as being anticipated by Carr et al. (U.S. Patent No. 6,600,744).

Regarding Claim 1, Carr et al. discloses a method for classifying a data packet in a network interface, comprising the steps of: (a) receiving a plurality of classification parameters (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. The key from the relevant header of the packet received corresponds to receiving a plurality of classification parameters);

(b) generating a plurality of program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification parameter (Fig. 1, Fig. 3, Fig. 4; col 2, lines 31-36. The rules or parameters for

Art Unit: 2616

classifying the packets are stored in a memory structure. The memory structure receives a set of rule selection signals, and provides a selected set of rules to a comparison block in response to the rule selection signals. The comparison block also receives a key that includes the relevant information for classifying the packet according to the rule set stored in the memory. The rules corresponds to a plurality of program modules and the comparison block which receives a key that includes the relevant information for classifying the packet according to the rule is associated with plurality of program modules for testing for adherence to at least one corresponding classification parameter);

- (c) receiving the data packet (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. Receiving data packet is shown in Fig.1, element 10);
- (d) generating a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more redefined fields in the data packet when present (Fig.1, Fig. 3, Fig. 4; col 1, lines 42-50; col 3, line 43 through col 4, line 6). Key 24 and the rule selection signals 22 are generated by a key generation block 20. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the

Art Unit: 2616

particular classification operation. As stated earlier, the rule selection signals 22 may be determined based on a number of different factors related to the packet. The key generation block 20 which extracts fields from the header to generate the key is associated with generating a header, header indicating whether one or more predefined fields are present in the data packet and identifying a location of one or more redefined fields in the data packet when present);

- (e) executing each of said plurality of program modules, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of the data packet (Fig.1, Fig. 3, Fig. 4; col 2, lines 38-43. The comparison block compares the key to each of the rules in the selected set of rules, and when a favorable comparison is determined, the comparison block provides an indication of the favorable comparison is associated with executing each of plurality of program modules, wherein each of plurality of program modules receives header and generates a test result based on contents of header and contents of the data packet. Note: The contents of header and contents of data packet are inherently considered to be the entire packet received (element 10)); and
- (f) processing the data packet based on said test results from said plurality of program modules (Fig.1, Fig. 3, Fig. 4; col 2, lines 43-48. A prioritization block operably coupled to the comparison block prioritizes the rules that resulted in favorable comparisons to determine a preferred rule, where the preferred rule includes the resulting classification information for the packet is associated with

Art Unit: 2616

processing the data packet based on test results from plurality of program modules).

Regarding Claim 4, Carr et al. discloses wherein step (f) comprises transmitting the data packet over a selected service flow based on said test results from said plurality of program modules (col 4, lines 5-13. The packet classification engine can be structured such that multiple matches between the key and the rule set are determined for each key value. Thus, one class of rules may be utilized to determine the billing class for a packet, whereas another class of rules may be used to determine the forwarding characteristics for the packet which correspond to transmitting the data packet over a selected service flow based on said test results from plurality of program modules).

Regarding Claim 5, Carr et al. discloses wherein step (f) comprises rejecting the data packet for violating classification parameters based on said test results from said plurality of program modules (col 4, lines 31-54. When the rules are used for comparison with the key 24, and a rule is determined as the preferable rule, the result data corresponding to that rule is included in the output of the packet classification engine. For example, if a packet is classified based on its destination address, the results of a favorable comparison with a rule in the memory array 40 may be to allow the data communication packet to pass through the switch making decisions based on the packet classification which can be associated with an unfavorable comparison comprises rejecting the data packet for violating classification parameters based on test results from

plurality of program modules).

Regarding Claim 10, Carr et al. discloses wherein said steps (a) and (b) occur during generation of a new service flow (col 8, line 65 through col 9, line 17. When using a time of day parameter in determining whether or not certain data packets should be passed. For example, during business hours a particular user may not be allowed to receive data packets from a particular source. However, when business hours are over, the lookup table could be updated to point to a new set of rules that allow for such data packets to be passed. As such, data packets associated with a specific source or specific protocol may be disallowed during certain times of day, and allowed during other times of day are associated with steps (a) and (b) occurring during generation of a new service flow).

Regarding Claim 11, Carr et al. discloses wherein said header is concatenated to the data packet (Fig. 1 element 10; col 1, lines 42-46. Note: It is inherent that the data packet contains header and payload fields. Therefore, a header is inherently concatenated to the payload forming a data packet).

Regarding Claim 12, Carr et al. discloses wherein step (e) comprises executing each of said plurality of program modules in parallel (col 2, lines 49-56. Implementing the packet classification engine using a memory that stores many rules and provides a large number of these rules to the comparison block in parallel, many rules can be

Art Unit: 2616

compared with the key simultaneously is associated with executing each of said plurality of program modules in parallel).

Regarding Claim 13, Carr et al. discloses wherein step (f) comprises the steps of: combining said test results from said plurality of program modules using a logical AND operation (Fig. 2; col 7, lines 61-64. The outputs of all of the comparators are combined by the AND gate 120 such that all of the comparators must determine a favorable result to produce a match 122 between the key 24 and the rule 42 are associated with combining test results from plurality of program modules using a logical AND operation); and processing the data packet based on a result of said logical AND operation (col 8, lines 11-20).

Regarding Claim 14, Carr et al. discloses a method for classifying a data packet in a network interface, comprising the steps of: (a) receiving a plurality of classification parameters (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts

fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. The key from the relevant header of the packet received corresponds to receiving a plurality of classification parameters); (b) generating a plurality of optimized program modules, each of said plurality of program modules for testing for adherence to at least one corresponding

Art Unit: 2616

classification parameter (Fig.1, Fig. 3, Fig. 4; col 2, lines 31-36. The rules or parameters for classifying the packets are stored in a memory structure. The memory structure receives a set of rule selection signals, and provides a selected set of rules to a comparison block in response to the rule selection signals. The comparison block also receives a key that includes the relevant information for classifying the packet according to the rule set stored in the memory. The rules corresponds to a plurality of program modules and the comparison block which receives a key that includes the relevant information for classifying the packet according to the rule is associated with plurality of program modules for testing for adherence to at least one corresponding classification parameter);

- (c) receiving the data packet (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation, Receiving data packet is shown in Fig.1, element 10);
- (d) generating a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more predefined fields in the data packet when present (Fig.1, Fig. 3, Fig. 4; col 1, lines 42-50; col 3, line 43 through col 4, line 6. Key 24 and the rule selection signals 22 are generated by a key generation block 20. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to

Art Unit: 2616

generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. As stated earlier, the rule selection signals 22 may be determined based on a number of different factors related to the packet. The key generation block 20 which extracts fields from the header to generate the key is associated with generating a header, header indicating whether one or more predefined fields are present in the data packet and identifying a location of one or more redefined fields in the data packet when present);

(e) serially executing said plurality of program modules, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of the data packet used to generate the header, until one of said plurality of program modules generates a failing test result (Fig. 1, Fig. 3, Fig. 4; col 2, lines 38-43; col 11, line 29 through col 12, line 8; col 13, line 67 through col 14, lines 8. The comparison block compares the key to each of the rules in the selected set of rules, and when a favorable comparison is determined, the comparison block provides an indication of the favorable comparison is associated with executing each of plurality of program modules, wherein each of plurality of program modules receives header and generates a test result based on contents of header and contents of the data packet. The sequencer 250 receives indications from the scheduler 240 that a new key has been received and is to be compared with a certain rule set. The sequencer passes the start index to the lookup table 272 to select the first address offset that is passed to the data array 290. Sequencer 250 correspond to

serially executing plurality of program modules. Fig. 4, step 422. If the linked list is no longer supplying additional address offsets to retrieve additional rule sets, the system may return a value indicating that no match has been achieved and this corresponds to plurality of program modules generates a failing test result Note: The contents of header and contents of data packet are inherently considered to be the entire packet received (element 10)); and (f) processing the data packet based on whether a failing test result was generated in step (e) (Fig.1, Fig. 3, Fig. 4; col 2, lines 43-48; col 14, lines 8-15. A prioritization block operably coupled to the comparison block prioritizes the rules that resulted in favorable comparisons to determine a preferred rule, where the preferred rule includes the resulting classification information for the packet is associated with processing the data packet based on test results from plurality of program modules).

Regarding Claim 15, Carr et al. discloses a method for classifying a data packet in a network interface, comprising the steps of: (a) receiving a plurality of classification parameters (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. The key from the relevant header of the packet received corresponds to receiving a plurality of classification parameters);

(b) generating a plurality of program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification

parameter (Fig.1, Fig. 3, Fig. 4; col 2, lines 31-36. The rules or parameters for classifying the packets are stored in a memory structure. The memory structure receives a set of rule selection signals, and provides a selected set of rules to a comparison block in response to the rule selection signals. The comparison block also receives a key that includes the relevant information for classifying the packet according to the rule set stored in the memory. The rules corresponds to a plurality of program modules and the comparison block which receives a key that includes the relevant information for classifying the packet according to the rule is associated with plurality of program modules for testing for adherence to at least one corresponding classification parameter);

- (c) receiving the data packet (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. Receiving data packet is shown in Fig.1, element 10);
- (d) executing each of said plurality of program modules, wherein each of said plurality of program modules generates a test result based on contents of the data packet (Fig.1, Fig. 3, Fig. 4; col 2, lines 38-43. The comparison block compares the key to each of the rules in the selected set of rules, and when a favorable comparison is determined, the comparison block provides an indication of the favorable

comparison is associated with executing each of said plurality of program modules, wherein each of plurality of program modules generates a test result based on contents of the data packet Note: The contents of data packet are inherently considered to be the entire packet received (element 10) including the header); and

(e) processing the data packet based on said test results from said plurality of program modules (Fig.1, Fig. 3, Fig. 4; col 2, lines 43-48. A prioritization block operably coupled to the comparison block prioritizes the rules that resulted in favorable comparisons to determine a preferred rule, where the preferred rule includes the resulting classification information for the packet is associated with processing the data packet based on test. results from plurality of program modules).

Regarding Claim 18, Carr et al. discloses wherein step (e) comprises transmitting the data packet over a selected service flow based on said test results from said plurality of program modules (col 4, lines 5-13. The packet classification engine can be structured such that multiple matches between the key and the rule set are determined for each key value. Thus, one class of rules may be utilized to determine the billing class for a packet, whereas another class of rules may be used to determine the forwarding characteristics for the packet which correspond to transmitting the data packet Over a selected service flow based on said test results from plurality of program modules).

Art Unit: 2616

Regarding Claim 19, Carr et al. discloses wherein step (e) comprises rejecting the data packet for violating classification parameters based on said test results from said plurality of program modules (col 4, lines 31-54. When the rules are used for comparison with the key 24, and a rule is determined as the preferable rule, the result data corresponding to that rule is included in the output of the packet classification engine. For example, if a packet is classified based on its destination address, the results of a favorable comparison with a rule in the memory array 40 may be to allow the data communication packet to pass through the switch making decisions based on the packet classification which can be associated with an unfavorable comparison comprises rejecting the data packet for violating classification parameters based on test results from plurality of program modules).

Regarding Claim 24, Carr et al. discloses wherein said steps (a) and (b) occur during generation of a new service flow (col 8, line 65 through col 9, line 17. When using a time of day parameter in determining whether or not certain data packets should be passed. For example, during business hours a particular user may not be allowed to receive data packets from a particular source. However, when business hours are over, the lookup table could be updated to point to a new set of rules that allow for such data packets to be passed. As such, data packets associated with a specific source or specific protocol may be disallowed during certain times of day, and allowed during other times of day are associated with steps (a) and (b) occurring during generation of a new service flow).

Page 15

Art Unit: 2616

Regarding Claim 25, Carr et al. discloses wherein step (d) comprises the step of: executing each of said plurality of program modules in parallel (col 2, lines 49-56. Implementing the packet classification engine using a memory that stores many rules and provides a large number of these rules to the comparison block in parallel, many rules can be compared with the key simultaneously is associated with executing each of said plurality of program modules in parallel).

Regarding Claim 26, Carr et al. discloses wherein step (e) comprises the steps of: (1) combining said test results from said plurality of program modules using a logical AND operation (Fig. 2; col 7, lines 61-64. The outputs of all of the comparators are combined by the AND gate 120 such that all of the comparators must determine a favorable result to produce a match 122 between the key 24 and the rule 42. are associated with combining test results from plurality of program modules using a logical AND operation); and (2) processing the data packet based on a result of said logical AND operation (col 8, lines 11-20).

Regarding Claim 27, Carr et al. discloses a computer program product comprising a computer usable medium having computer program logic for enabling a processor in a network interface to classify a data packet (col 2, lines 57-66. The packet classification engine may be implemented using dynamic random access memory (DRAM) technology. The rule set stored within the memory structure may be modified through a simple memory access that alters the specific rules within memory. Additionally, the signals utilized to select the

Page 16

Art Unit: 2616

set of rules for a particular comparison can be mapped to different locations within the memory structure, thus allowing different sets of rules to be utilized in different sets of conditions. Similarly, the mapping of the rule selection signals to a specific set of rules is flexible enough that a plurality of different rule sets can be included in the memory structure, allowing a variety of protocols to be supported in a single packet classification engine. Note: Dynamic random access memory (DRAM) technology and the signals utilized to select the set of rules are inherently associated with a computer program product comprising a computer usable medium having computer program logic for enabling a processor in a network interface to classify a data packet) comprising: a first means for enabling the processor to receive a plurality of classification parameters (Fig. 1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation. The key from the relevant header of the packet received corresponds to receiving a plurality of classification parameters); a second means for enabling the processor to generate a plurality of program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification parameter (Fig. 1, Fig. 3, Fig. 4; col 2, lines 31-36). The rules or parameters for classifying the packets are stored in a memory structure. The memory structure receives a set of rule selection signals, and provides a selected set of rules to a comparison block in response to the rule selection signals. The comparison block also receives a key that includes the

Art Unit: 2616

relevant information for classifying the packet according to the rule set stored in the memory. The rules corresponds to a plurality of program modules and the comparison block which receives a key that includes the relevant information for classifying the packet according to the rule is associated with plurality of program modules for testing for adherence to at least one corresponding classification parameter);

a third means for enabling the processor to receive the data packet (Fig.1, Fig. 3, Fig. 4; col 4, lines 2-6. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation.

Receiving data packet is shown in Fig.1, element 10);

a fourth means for enabling the processor to generate a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more predefined fields of the data packet when present (Fig.1, Fig. 3, Fig. 4; col 1, lines 42-50; col 3, line 43 through col 4, line 6). Key 24 and the rule selection signals 22 are generated by a key generation block 20. The key generation block 20 receives the packet 10, or at least the relevant header information for the packet, and extracts fields from the header to generate the key. Various portions of various fields may be used to generate the key that is appropriate for the particular classification operation.

As stated earlier, the rule selection signals 22 may be determined based on a number of different factors related to the packet. The key generation block 20 which extracts fields from the header to generate the key is associated with generating a header, header indicating whether one or more predefined fields are present in the data packet and identifying a location of one or more redefined fields in the data packet when present);

a fifth means for enabling the processor to execute each of said plurality of program modules, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of said data packet (Fig.1, Fig. 3, Fig. 4; col 2, lines 38-43. The comparison block compares the key to each of the rules in the selected set of rules, and when a favorable comparison is determined, the comparison block provides an indication of the favorable comparison is associated with executing each of plurality of program modules, wherein each of plurality of program modules receives header and generates a test result based on contents of header and contents of the data packet. Note: The contents of header and contents of data packet are inherently considered to be the entire packet received (element 10)); and

a sixth means for enabling the processor to process the data packet based on said test results from said plurality of program modules (Fig.1, Fig. 3, Fig. 4; col 2, lines 43-48. A prioritization block operably coupled to the comparison block prioritizes

Art Unit: 2616

the rules that resulted in favorable comparisons to determine a preferred rule, where the preferred rule includes the resulting classification information for the packet is associated with processing the data packet based on test results from plurality of program modules).

## Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 2, 6-9, 16, 20-23, 28, 30-39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Carr et al.(U.S. Patent No. 6,600,744) in view of Synnestvedt et at. (U.S. Patent No. 6,598,057).

Regarding Claim 2, Carr et al. discloses all the limitations of claim 1.

Carr et al. does not disclose wherein said classification parameters comprise DOCSIS classification parameters.

Synnestvedt et al. discloses classification parameters comprising DOCSIS classification parameters (Fig. 2, element 206; col 3, lines 44-48; col 4, lines 8-20).

At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as

Art Unit: 2616

allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 6, Carr et al. discloses all the limitations of claim 1. Carr et at. does not disclose wherein step (a) comprises receiving a configuration file, said configuration file including said plurality of classification parameters. Synnestyedt et al. discloses wherein step (a) comprises receiving a configuration file, said configuration file including said plurality of classification parameters (Fig. 2; col 4, lines 9-20. The DOCSISFile class 206 inherits from DynamicFile class 204, and represents a DOCSIS compliant configuration file which corresponds to receiving a configuration file, configuration file including plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 7, Carr et al. discloses all the limitations of claim 1.

Carr et al. does not disclose wherein step (a) comprises receiving a cable

Art Unit: 2616

modem configuration request, said cable modem configuration request including said plurality of classification parameters. Synnestvedt et al. discloses wherein step (a) comprises receiving a cable modem configuration request, said cable modem configuration request including said plurality of classification parameters (Fig. 1; col 3, lines 44-48; col 4, lines 5-8). Requests for configuration originate at cable modem 102 and travel to TFTP (Trivial File Transfer Protocol) server 124, where a DOCSIS binary configuration file is generated and sent back to cable modem correspond to receiving a cable modem configuration request, cable modem configuration request including plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 8, Carr et al. discloses all the limitations of claim 1. Carr et al. does not disclose wherein step (a) comprises receiving a dynamic service message, wherein said dynamic service message includes said plurality of classification parameters. Synnestvedt et al. discloses wherein step (a) comprises receiving a dynamic service message, wherein said dynamic service message

Art Unit: 2616

includes said plurality of classification parameters (Fig. 4; col 5, lines 11-16. A DOCSIS configuration file is dynamically generated based upon a RRQ message received by an augmented TFTP (Trivial File Transfer Protocol) server 124 is associated with receiving a dynamic service message, wherein dynamic service message includes plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 9, Carr et al. discloses all the limitations of claim 1.

Carr et al. does not disclose wherein said steps (a) and (b) occur as part of a cable modem registration process. Synnestvedt et al. discloses wherein said steps (a) and (b) occur as part of a cable modem registration process (Fig. 4, steps 416, 418 and 420; col 3, lines 44-48; col 10, lines 16-18. Steps 416, 418 and 420 correspond to steps (a) and (b) occuring as part of a cable modem registration process). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning

Art Unit: 2616

introl (4diliber: 10/00/,//

through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 16, Carr et al. discloses all the limitations of claim 15. Carr et at. does not disclose wherein said classification parameters comprise DOCSIS classification parameters. Synnestvedt et al. discloses classification parameters comprise DOCSIS classification parameters (Fig. 2, element 206; col 3, lines 44-48; col 4, lines 8-20). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 20, Carr et al. discloses all the limitations of claim 15. Carr et al. does not disclose wherein step (a) comprises receiving a configuration file, said configuration file including said plurality of classification parameters. Synnestvedt et al. discloses wherein step (a) comprises receiving a configuration file, said configuration file including said plurality of classification parameters (Fig. 2; col 4, lines 9-20. The DOCSISFile class 206 inherits from DynamicFile class 204, and

represents a DOCSIS compliant configuration file which corresponds to receiving a configuration file, configuration file including plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file

standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 21, Carr et al. discloses all the limitations of claim 15. Carr et al. does not disclose wherein step (a) comprises receiving a cable modem configuration request, said cable modem configuration request including said plurality of classification parameters. Synnestvedt et al. discloses wherein step (a) comprises receiving a cable modem configuration request, said cable modem configuration request including said plurality of classification parameters (Fig. 1; col 3, lines 44-48; col 4, lines 5-8). Requests for configuration originate at cable modem 102 and travel to TFTP (Trivial File Transfer Protocol) server 124, where a DOCSIS binary configuration file is generated and sent back to cable modem correspond to receiving

Page 25

Art Unit: 2616

a cable modem configuration request, cable modem configuration request including plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 22, Carr et al. discloses all the limitations of claim 15.

Carr et at. does not disclose wherein step (a) comprises receiving a dynamic service message, wherein said dynamic service message includes said plurality of classification parameters. Synnestvedt et al. discloses wherein step (a) comprises receiving a dynamic service message, wherein said dynamic service message includes said plurality of classification parameters (Fig. 4; col 5, lines 11-16. A DOCSIS configuration file is dynamically generated based upon a RRQ message received by an augmented TFTP (Trivial File Transfer Protocol) server 124 is associated with receiving a dynamic service message, wherein dynamic service

Art Unit: 2616

message includes plurality of classification parameters). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 23, Carr et al. discloses all the limitations of claim 15. Carr et al. does not disclose wherein said steps (a) and (b) occur as part of a cable modem registration process. Synnestvedt et al. discloses wherein said steps (a) and (b) occur as part of a cable modem registration process (Fig. 4, steps 416, 418 and 420; col 3, lines 44-48; col 10, lines 16-18. Steps 416, 418 and 420 correspond to steps (a) and (b) occuring as part of a cable modem registration process). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of

more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2, lines 63-65; col 3, lines 9-12).

Regarding Claim 28, Carr et al. discloses all the limitations of claim 27. Carr et al. does not disclose wherein said classification parameters comprise DOCSIS classification parameters. Synnestvedt et al. discloses classification parameters comprise DOCSIS classification parameters (Fig. 2, element 206; col 3, lines 44-48; col 4, linesl 8-20). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to include the DOCSIS classification parameters as taught by Synnestvedt et al. into the classification system of Carr et al. allowing for more effective broadband provisioning through better configuration file management as well as allowing for the creation of more flexible subscriber service plans wherein the resulting configuration can be generated according to the DOCSIS configuration file standard (col 2; lines 63-65; col 3, lines 9-12).

Art Unit: 2616

Regarding Claim 30, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Carr et al. discloses wherein said sixth means comprises means for enabling the processor to transmit the data packet over a selected service flow based on said test results from said plurality of program modules (col 4, lines 5-13. The packet classification engine can be structured such that multiple matches between the key and the rule set are determined for each key value. Thus, one class of rules may be utilized to determine the billing class for a packet, whereas another class of rules may be used to determine the forwarding characteristics for the packet which correspond to enabling the processor to transmit the data packet over a selected service flow based on said test results from said plurality of program modules).

Regarding Claim 31, Carr et al. and Synnestvedt et at. discloses all the limitations of claims 27 and 28. Further Carr et at. discloses wherein said sixth means comprises means for enabling the processor to reject the data packet for violating classification parameters based on said test results from said plurality of program modules (col 4, lines 31-54. When the rules are used for comparison with the key 24, and a rule is determined as the preferable rule, the result data corresponding to that rule is included in the output of the packet classification engine. For example, if a packet is classified based on its destination address, the results of a favorable comparison with a rule in the memory array 40 may be to allow the data communication packet to pass through the switch making decisions based on the

packet classification which can be associated with an unfavorable comparison comprises rejecting the data packet for violating classification parameters based on test results from plurality of program modules).

Regarding Claim 32, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Synnestvedt et at. discloses wherein said first means comprises means for enabling the processor to receive a plurality of classification parameters retrieved from a configuration file (Fig. 2; col 4, lines 9-20. The DOCSISFile class 206 inherits from DynamicFile class 204, and represents a DOCSIS compliant configuration file which corresponds to enabling the processor to receive a plurality of classification parameters retrieved from a configuration file).

Regarding Claim 33, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Synnestvedt et al. discloses wherein said first means comprises means for enabling the processor to receive a plurality of classification parameters retrieved from a cable modem configuration request (Fig. 1; col 3, lines 44-48; col 4, lines 5-8. Requests for configuration originate at cable modem 102 and travel to TFTP (Trivial File Transfer Protocol) server 124, where a DOCSIS binary configuration file is generated and sent back to cable modem correspond to enabling the processor to receive a plurality of classification parameters retrieved from a cable modem configuration request).

Regarding Claim 34, Carr et at. and Synnestvedt et at. discloses all the limitations of claims 27 and 28. Further Synnestvedt et al. discloses wherein said first means comprises means for enabling the processor to receive a plurality of classification parameters retrieved from a dynamic service message (Fig. 4; col 5, lines 11-16. A DOCSIS configuration file is dynamically generated based upon a RRQ message received by an augmented TFTP (Trivial File Transfer Protocol) server 124 is associated with enabling the processor to receive a plurality of classification parameters retrieved from a dynamic service message).

Regarding Claim 35, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Synnestvedt et al. discloses wherein said first means and said second means are executed as part of a cable modem registration request (Fig. 4, steps 416, 418 and 420; col 3, lines 44-48; col 10, lines 16-18. Steps 416, 418 and 420 correspond to steps (a) and (b) occurring as part of a cable modem registration request).

Regarding Claim 36, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Carr et al. discloses wherein said first means and said second means are executed during generation of a new service flow (col 8, line 65 through col 9, line 17. When using a time of day parameter in determining whether or not certain data packets should be passed. For example, during business hours a particular user may not be allowed to receive data packets from a particular source. However, when

business hours are over, the lookup table could be updated to point to a new set of rules that allow for such data packets to be passed. As such, data packets associated with a specific source or specific protocol may be disallowed during certain times of day, and allowed during other times of day are associated with first means and second means executed during generation of a new service flow).

Regarding Claim 37, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Carr et al. discloses wherein said fourth means comprises means for enabling the processor to concatenate said header to the data packet (Fig. 1 element 10; col 1, lines 42-46. Note: It is inherent that the data packet contains header and payload fields. Therefore, a header is inherently concatenated to the payload forming a data packet).

Regarding Claim 38, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Carr et al. discloses wherein said fifth means comprises means for enabling the processor to execute each of said plurality of program modules in parallel (col 2, lines 49-56. Implementing the packet classification engine using a memory that stores many rules and provides a large number of these rules to the comparison block in parallel, many rules can be compared with the key simultaneously is associated with

enabling the processor to execute each of plurality of program modules in parallel).

Regarding Claim 39, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Further Carr et al. discloses wherein said sixth means comprises means for enabling the processor to combine said test results from said plurality of program modules using a logical AND operation and process the data packet based on a result of said logical AND operation (Fig. 2; col 7, lines 61-64. The outputs of all of the comparators are combined by the AND gate 120 such that all of the comparators must determine a favorable result to produce a match 122 between the key 24 and the rule 42. are associated with combining test results from plurality of program modules using a logical AND operation. Col 8, lines 11-20 is associated with processing the data packet based on a result of said logical AND operation).

7. Claims 3, 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Carr et al. (U.S. Patent No. 6,600,744) in view of Connery et al. (U.S. Patent No. 6,570,884).

Regarding Claim 3, Carr et al. discloses all the limitations of claim 1. Carr et al. does not disclose wherein step (f) comprises applying packet header suppression to the data packet based on said test results from said plurality of program modules. Connery et al. discloses wherein step (f) comprises applying packet header suppression to the data packet based on said test results from said plurality of program modules. (col 8, lines 53-57. For the pattern matching engines to have an optional capability to treat an incoming SNAP encapsulated IP packet as if it were an EtherType encapsulation. For this type of packet, the SNAP header is ignored in the pattern matching process. Ignoring the SNAP header in the pattern matching process is associated with packet header suppression to the data packet based on test results from plurality of program modules). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to apply the teachings of Connery et al. into the system of Carr et al. such that the processor is only required to handle packet identified by the dedicated packet filter logic, it need not have the capability to keep up with the entire data stream (col 2, lines 13-16).

Regarding Claim 17, Carr et al. discloses all the limitations of claim 15. Carr et al. does not disclose wherein step (e) comprises applying packet header suppression to the data packet based on said test results from said plurality of program modules. Connery et al. discloses wherein step (e) comprises applying packet header suppression to the data packet based on said-test results from said

plurality of program modules. (col 8, lines 53-57. For the pattern matching engines to have an optional capability to treat an incoming SNAP encapsulated IP packet as if it were an EtherType encapsulation. For this type of packet, the SNAP header is ignored in the pattern matching process. Ignoring the SNAP header in the pattern matching process is associated with packet header suppression to the data packet based on test results from plurality of program modules). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to apply the teachings of Connery et al. into the system of Carr et al. such that the processor is only required to handle packets identified by the dedicated packet filter logic, it need not have the capability to keep up with the entire data stream (col 2, lines 13-16).

8. Claim 29 is rejected under 35 U.S.C. 103(a) as being unpatentable over Carr et al.(U.S. Patent No. 6,600,744) in view of Synnestvedt et at. (U.S. Patent No. 6,598,057) and further in view of Connery et al. (U.S. Patent No. 6,570,884).

Regarding Claim 29, Carr et al. and Synnestvedt et al. discloses all the limitations of claims 27 and 28. Carr et al. and Synnestvedt et al. does not disclose wherein said sixth means comprises means for enabling the processor to apply packet header suppression to the data packet based on said test results from said plurality of program modules. Connery et al. discloses wherein said sixth means comprises means for enabling the processor to apply packet header suppression to

Application/Control Number: 10/087,779 Page 35

Art Unit: 2616

the data packet based on said test results from said plurality of program modules. (col 8, lines 53-57. For the pattern matching engines to have an optional capability to treat an incoming SNAP encapsulated IP packet as if it were an EtherType encapsulation. For this type of packet, the SNAP header is ignored in the pattern matching process. Ignoring the SNAP header in the pattern matching process is associated with packet header suppression to the data packet based on test results from plurality of program modules). At the time the invention was made it would have been obvious to a person of ordinary skill in the art to apply the teachings of Connery et al. into the system of Carr et al. and Synnestvedt et al. such that the processor is only required to handle packets identified by the dedicated packet filter logic, it need not have the capability to keep up with the entire data stream (col 2, lines 13-16).

### Response to Arguments

- 9. Applicant's arguments filed 11/15/2006 have been fully considered but they are not persuasive.
  - On pgs. 1-5 of the Pre-Appeal Brief Request, Applicant contends that Carr does not disclose generating a plurality of program modules to test for adherence to at least one corresponding classification parameter. Applicant argues that the stored rules/parameters and their subsequent use by comparison block 50 in Carr does not meet the claimed "program modules" because

Carr discloses the various testing operations performed at comparison block 50 are preferably implemented in hardware, whereas the claimed "program modules" claimed by Applicant are implemented in software.

- In response to applicant's argument that the references fail to show certain features of applicant's invention, it is noted that the features upon which applicant relies (software versus hardware implementation as well as the modification and re-ordering of testing operations) are not recited in the rejected claim(s).

  Although the claims are interpreted in light of the specification, limitations from the specification are not read into the claims. See *In re Van Geuns*, 988 F.2d 1181, 26 USPQ2d 1057 (Fed. Cir. 1993). Furthermore, as shown in the Advisory Action filed 10/3/2006, Carr shows that the various components shown in Fig. 3 are implemented through logic on DRAM process, known in the art to be a software application that meets the disclosure of Applicant's generated "program modules" (also see the rejection of Claim 27 above, pg. 15-16).
- On pgs. 1-5 of the Pre-Appeal Brief Request, Applicant contends that Carr does not disclose performing the claim limitations at a network interface.

In response to applicant's arguments, the recitation "network interface" has not been given patentable weight because the recitation occurs in the preamble. A preamble is generally not accorded any patentable weight where it merely recites the purpose of a process or the intended use of a structure, and where the body of the claim does not depend on the preamble for completeness but, instead, the process steps or structural limitations are able to stand alone. See *In re Hirao*, 535 F.2d 67, 190 USPQ 15 (CCPA 1976) and *Kropa v. Robie*, 187 F.2d 150, 152, 88 USPQ 478, 481 (CCPA 1951). However, Carr shows that the disclosed packet processing is based upon examining the headers of the packets at various points in the network (Col. 1, lines 16-18). Therefore, even if the recitation of "network interface" where placed in the body of the claim, it would be met by the disclosure of Carr.

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Gregory B. Sefcheck whose telephone number is 571-272-3098. The examiner can normally be reached on Monday-Friday, 8:00am-4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Seema Rao can be reached on 571-272-3174. The fax

Application/Control Number: 10/087,779 Page 38

Art Unit: 2616

phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

GBS 655 1-9-2007

SUPERVISORY PATENT EXAMINED TECHNOLOGY CENTER 2600